

1 Technical data

			90/40-621C			
Actuation modes:	Contact actuation	Depth adjustment: Weight (without fasteners)(kg):		No		
Height/ length (mm):	198 / 248			1,34		
Min/max operating pressure (bar):	5 - 8	Air consumption per driving operation:		0,9 I at 6 bar		
Noise characteristics (according	to EN12549:1999):	L _{pA} , _{1s} 81 dB(A)	L _{WA} , _{1s} 83,6 dB(A)	K pA and K WA 2,5 dB(A)		
Vibration value (according to ISO 28927-13:2022-02):		a _{hd} 1,63 m/s²		K _a 0,44 m/s²		
Fasteners				Staple 90		
Length (mm):				15 - 40		
Wire diameter (mm):				1,05 x 1,25		
Crown width (mm):				5,7		
Scope of delivery	Pneumatic nailer, General operating instructions, device-specific information, Allen key					

2 Safety advices




Risk of most severe injuries from nailers!

Any person operating the nailer must have read and understood both the following device-specific information as well as the General operation instructions for pneumatic nailers! Always have both documents ready!



Operating the device without knowing the General operating instructions is forbidden! Resulting problems extinct any possible claims against the manufacturer.

3 Safe resting position



- Whenever not in use, safely put down the device on its left or right side according to adjacent symbol picture (see Chap. 1.3 of General operating instructions).
- . Do not put down the device on another side.
- Also when putting down or lifting up, never point the driving nose at persons or animals.


F	front	В	back	
L	left	R	right	
Т	top	U	underside	

Device-specific additional instructions for nailer 90/40 - 621C



4 Filling the magazine

- Ensure that nailer and fasteners are compatible (Chap. 1) with each other.
- Check fasteners for proper condition.
- Pull pusher 1 backwards and engage. Insert staple rod into the magazine from above and push forward. Disengage the pusher and push it forward.



5 EU Declaration of conformity

The BeA GmbH, manufacturer or importer, address as on cover sheet, declares under sole responsibility this product's conformity with all relevant provisions of the EU Machine Directive 2006/42/EG. The following standards are applied: EN ISO 12100:2010 (Machine safety); ISO 11148-13:2017-11 (Hand-held non-el. machines - Fastener driving tools); EN 12549:1999+A1:2008 (Noise measuring for driving tools); ISO 28927-13:2022-02 (Vibrations at driving tools).

Jog Natuste

Dr. Jörg Dalhöfer, CEO

of the same

Joachim Bauer, Documentation responsible